



3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
	20 bar
	0,82 cc
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	See Performance Data
	31,8 mm
	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: DOHDEHN

(E)

(H)

(N)

E 4-**SAE**

H 300 psi (20 bar)

N
V

TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 300 psi (20 bar)
- 145 psi 10 bar
- SAE 4 10 / 0.7 cc/min Sun DAA*-***
- 1 2
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 1 2 3
- 5000 psi (350 bar)
- Sun /

PERFORMANCE CURVES

