



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-23A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	20 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Pilot Volume Displacement	0,82 cc
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

OPTION SELECTION EXAMPLE: DOHSXHN

CONTROL	(X)	MINIMUM PILOT PRESSURE	(H)	SEAL MATERIAL	(N)	MATERIAL/COATING
X	piloto estándar	H	300 psi (20 bar)	N	Buna-N	Standard Material/Coating
				E	EPDM	/AP Stainless Steel, Passivated
				V	Viton	/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

