



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-19A
Series	4
Capacity	480 L/min.
Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	20 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Pilot Volume Displacement	2,8 cc
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

OPTION SELECTION EXAMPLE: DOJCEHN

CONTROL

- E** External 4-SAE Drain Port
- X Standard Pilot, Atmospheric Vent

(E) MINIMUM PILOT PRESSURE

- H** 300 psi (20 bar)

(H) SEAL MATERIAL

- N** Buna-N
- E EPDM
- V Viton

(N)

PERFORMANCE CURVES

