



3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-24A
	4
	480 L/min.
	350 bar
	20 bar
	2,8 cc
110 SUS (24 cSt)	0,7 cc/min.@350 bar
	41,3 mm
	474 - 508 Nm
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

OPTION SELECTION EXAMPLE: DOJSXHN

	(X)	(H)	(N)	MATERIAL/COATING
	X	H 300 psi (20 bar)	N	Standard Material/Coating
			E EPDM	/AP
			V	/LH -

TECHNICAL FEATURES

- 1 2 5000 psi (350 bar) 300 psi (20 bar)
- 1 2 3 4 3 4
-
- 1 2 5000psi 10 / 350bar 0,7 cc/min
- 145 psi 10 bar
- 1 2
- EPDM
- 5000 psi (350 bar)
- Sun /

PERFORMANCE CURVES

