



2

1 3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	28 L/min.
	350 bar
110 SUS (24 cSt)	15 cc/min. @70 bar
	15 L/min.
	0,11 - 0,16 L/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.15 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • 0 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: DPBBLAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
O			V	/AP

## TECHNICAL FEATURES

- 3 3 3 4
- 
- 
- 
- Sun

## PERFORMANCE CURVES

