



2

1 4

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	28 L/min.
	350 bar
110 SUS (24 cSt)	15 cc/min.@70 bar
	15 L/min.
	0,11 - 0,16 L/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,30 kg
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: DPBNLANV

(L)

(A)

(N)

L	A	N
C -	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N
	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V
	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	J 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)	
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)	

TECHNICAL FEATURES

- 4
- 3
-
- 4
-
- 3 3000psi 210bar
-
- Sun

PERFORMANCE CURVES

