



3 1 2 3

1 4

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
110 SUS (24 cSt)	15 cc/min. @70 bar
	15 L/min.
	0,11 - 0,16 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

CONFIGURATION OPTIONS

Model Code Example: DPBOLANV

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
C -	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	/AP
	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	J 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)		
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		