



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
110 SUS (24 cSt)	15 cc/min. @70 bar
	15 L/min.
	0,16 - 0,25 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

: • O 1 0.75 in. (19 mm)

CONFIGURATION OPTIONS

Model Code Example: DPCALAN

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
C	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	
K	C 150 - 6000 psi (10,5 - 420 bar), 3000 psi (210 bar)		
O	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	W 100 - 4500 psi (7 - 315 bar), 1000 psi (70 bar)		