



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                      |                           |
|----------------------|---------------------------|
|                      | T-2A                      |
|                      | 2                         |
|                      | 60 L/min.                 |
|                      | 350 bar                   |
| 110 SUS (24 cSt)     | 15 cc/min.@70 bar         |
|                      | 15 L/min.                 |
|                      | 0,16 - 0,25 L/min.        |
| -                    | 5                         |
|                      | 28,6 mm                   |
|                      | 61 - 68 Nm                |
|                      | 4 mm                      |
|                      | 15 mm                     |
|                      | 9 - 10 Nm                 |
|                      | 0.27 kg.                  |
| Seal kit - Cartridge | Buna: 990-202-007         |
| Seal kit - Cartridge | Polyurethane: 990-002-002 |
| Seal kit - Cartridge | Viton: 990-202-006        |
| Seal kit - Cartridge | Buna: 990-202-007         |
| Seal kit - Cartridge | Polyurethane: 990-002-002 |
| Seal kit - Cartridge | Viton: 990-202-006        |

: • 0 1 0.75 in. (19 mm)

## OPTION SELECTION EXAMPLE: DPCBLAN

|     |   |     |                           |
|-----|---|-----|---------------------------|
| (L) | (A)   | (N) | MATERIAL/COATING          |
| L   | A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) | N   | Standard Material/Coating |
| O   |   | V   | /AP                       |

### TECHNICAL FEATURES

- 3                                        3                                        3     4
- 
- 
- 3                                        3000psi 210bar
- 
- Sun

### PERFORMANCE CURVES

