



2

1 4

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	60 L/min.
	350 bar
110 SUS (24 cSt)	15 cc/min.@70 bar
	15 L/min.
	0,16 - 0,25 L/min.
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,30 kg
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: DPCMLANV

	(L)	(A)	(N)	MATERIAL/COATING
L	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
C	B	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	/LH -
	D	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
	E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	W	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		

TECHNICAL FEATURES

- 4
- 3
-
- 4
-
- 3 3000psi 210bar
-
- Sun

PERFORMANCE CURVES

