



in. (mm)

2

1 4

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	60 L/min.
	350 bar
110 SUS (24 cSt)	15 cc/min.@70 bar
	15 L/min.
	0,16 - 0,25 L/min.
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,30 kg
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

# OPTION SELECTION EXAMPLE: DPCNLANV

(L)

(A)

(N)

<b>L</b>	<b>A</b>	<b>N</b>
<b>C</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>V</b>
	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	
	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)	

## TECHNICAL FEATURES

- 4
- 3
- 
- 4
- 
- 3                    3000psi 210bar
- 
- Sun

## PERFORMANCE CURVES

