



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-21A |
| | 1 |
| | 2 L/min. |
| | 350 bar |
| | 20 drops/min. |
| | >85% of setting |
| | 22,2 mm |
| | 41 - 47 Nm |
| | 4 mm |
| | 15 mm |
| | 9 - 10 Nm |
| | 0.20 kg. |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |

OPTION SELECTION EXAMPLE: DRAYLAN

| | (L) | (A) | (N) | MATERIAL/COATING |
|---|-----|--|-----|---------------------------|
| L | A | 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) | N | Standard Material/Coating |
| | | C | V | /AP |
| | | 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar) | | |

TECHNICAL FEATURES

- 1 4
- 2 3 20 / 1.4cc/min
-
- Sun

PERFORMANCE CURVES

