



2

1 3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
110 SUS (24 cSt)	30 cc/min.
	15 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • O 1 0.75 in. (19 mm)

**CONFIGURATION OPTIONS**

Model Code Example: DRBBLANV

(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)	<b>N</b>	Standard Material/Coating
<b>C</b> -	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	<b>V</b>	/AP
	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		/LH -
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)		
	<b>W</b> 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)		