



Direct-acting, 3-way directional cartridges (1 blocked, 2 to 3 open) are switching devices typically used in moderate flow circuits. They can be used by themselves or to actuate larger pilot-operated directional cartridges or logic cartridges. The valve shifts when the pressure differential between port 1 and port 3 exceeds the setting.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Factory Pressure Settings Established at	4 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in <sup>3</sup> /min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

**NOTES:** • For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

**CONFIGURATION OPTIONS**

**Model Code Example: DRBCLANV**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting		V Viton		/AP Stainless Steel, Passivated
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting				/LH Mild Steel, Zinc-Nickel
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		W 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar) Standard Setting				