



3 1 2 3

1 4

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	28 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.
	15 L/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.18 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

: • O 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: DRBOLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b> <b>C</b> - <b>K</b> <b>O</b>		<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)	<b>N</b> <b>V</b>	Standard Material/Coating /AP
		<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)		
		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)		
		<b>W</b> 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)		

## TECHNICAL FEATURES

- 3
- 2 3
- 
- 
- 4
- 
- 1 2
- 3                    3000psi 210bar
- Sun

## PERFORMANCE CURVES

