



3 1 2 3

1 4

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	60 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.
	15 L/min.
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,25 kg
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

## OPTION SELECTION EXAMPLE: DRCOLANV

(L)

(A)

(N)

<b>L</b>	<b>A</b> 750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar)	<b>N</b>
<b>C</b> -	<b>B</b> 300 - 1500 psi (20 - 105 bar), 500 psi (35 bar)	<b>V</b>
	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)	

### TECHNICAL FEATURES

- 3
- 
- 
- 4
- 
- 3                    3000psi 210bar
- Sun

### PERFORMANCE CURVES

