



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-31A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Pilot Flow	0,38 L/min.
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0,20 kg
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006

# OPTION SELECTION EXAMPLE: DSCHXGHN

<b>CONTROL</b>	<b>(X) SHIFTING PRESSURE</b>	<b>(H) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>X</b> Not Adjustable	<b>H</b> 200 psi (14 bar) <b>G</b> 150 psi (10,5 bar)	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating <b>/LH</b> Mild Steel, Zinc-Nickel

## PERFORMANCE CURVES

