



CONFIGURATION

X	Control	Not Adjustable
C	Shifting Pressure	30 psi (2 bar)
N	Seal Material	Buna-N
	Material/Coating	

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

cavidad	T-31A
Series	1
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	15 cc/min.@70 bar
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.18 kg.
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006

OPTION SELECTION EXAMPLE: DSCLXCN

CONTROL	(X) SHIFTING PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C 30 psi (2 bar)	N Buna-N	Standard Material/Coating
	E 75 psi (5 bar)	V Viton	/LH Mild Steel, Zinc-Nickel
	F 100 psi (7 bar)		
	G 150 psi (10,5 bar)		

PERFORMANCE CURVES

