



CONFIGURATION

X	Control	Not Adjustable
G	Shifting Pressure	150 psi (10,5 bar)
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

NOTE:

cavidad	T-32A	DATA
Series	2	MAY
Capacity	80 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Pilot Flow	0,38 L/min.	
Valve Hex Size	28,6 mm	
Valve Installation Torque	61 - 68 Nm	
Model Weight	0.32 kg.	
Seal kit - Cartridge	Buna: 990-032-007	
Seal kit - Cartridge	Polyurethane: 990-032-002	
Seal kit - Cartridge	Viton: 990-032-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: DSEHXGN

CONTROL	(X) SHIFTING PRESSURE	(G) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	G 150 psi (10,5 bar) E 75 psi (5 bar) H 200 psi (14 bar)	N Buna-N V Viton	/LH Mild Steel, Zinc-Nickel /AP Stainless Steel, Passivated Standard Material/Coating

PERFORMANCE CURVES

