



PORT 1

CONFIGURATION

X	Control	Not Adjustable
G	Shifting Pressure	150 psi (10,5 bar)
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

NOTE:

cavidad	T-32A	DATA
Series	2	MAY
Capacity	80 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Pilot Flow	0,38 L/min.	
Valve Hex Size	28,6 mm	
Valve Installation Torque	61 - 68 Nm	
Model Weight	0.32 kg.	
Seal kit - Cartridge	Buna: 990-032-007	
Seal kit - Cartridge	Polyurethane: 990-032-002	
Seal kit - Cartridge	Viton: 990-032-006	
Seal kit - Cartridge	Buna: 990-032-007	
Seal kit - Cartridge	Polyurethane: 990-032-002	
Seal kit - Cartridge	Viton: 990-032-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: DSEHXGN

CONTROL	(X)	SHIFTING PRESSURE	(G)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
X Not Adjustable		G 150 psi (10,5 bar)		N Buna-N		/LH Mild Steel, Zinc-Nickel	
		H 200 psi (14 bar)		V Viton		/AP Stainless Steel, Passivated Standard Material/Coating	

PERFORMANCE CURVES

