



CONFIGURATION

| | | |
|---|-------------------|------------------|
| X | Control | Not Adjustable |
| H | Shifting Pressure | 200 psi (14 bar) |
| N | Seal Material | Buna-N |
| | Material/Coating | |

TECHNICAL DATA

| | |
|----------------------------|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Pilot Flow | 0,38 L/min. |
| Seal kit - Cartridge | Buna: 990-032-007 |
| Seal kit - Cartridge | Polyurethane: 990-032-002 |
| Seal kit - Cartridge | Viton: 990-032-006 |
| Seal kit - Cartridge | Buna: 990-032-007 |
| Seal kit - Cartridge | Polyurethane: 990-032-002 |
| Seal kit - Cartridge | Viton: 990-032-006 |

CONFIGURATION OPTIONS

Model Code Example: DSEHXHN

| CONTROL | (X) | SHIFTING PRESSURE | (H) | SEAL MATERIAL | (N) | MATERIAL/COATING | (/LH) |
|---------|----------------|-------------------|--------------------|---------------|--------|------------------|--|
| X | Not Adjustable | H | 200 psi (14 bar) | N | Buna-N | /LH | Mild Steel, Zinc-Nickel |
| | | G | 150 psi (10,5 bar) | V | Viton | /AP | Stainless Steel, Passivated Standard Material/Coating |