



**CONFIGURATION**

X	
H	200 psi (14 bar)
N	
Material/Coating	

2 4

NOTE: DATA MAY VARY FROM PART TO PART. SEE CONFIGURATION SECTION.

**TECHNICAL DATA**

	T-32A
	2
	80 L/min.
	350 bar
	0,38 L/min.
	28,6 mm
	61 - 68 Nm
	0.32 kg.
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006

## OPTION SELECTION EXAMPLE: DSEHXHN

	(X)	(H)	(N)	MATERIAL/COATING	(/LH)
<b>X</b>	<b>H</b> 200 psi (14 bar)	<b>N</b>	<b>/LH</b> -		
	D 50 psi (3,5 bar)	V	/AP		
	E 75 psi (5 bar)			Standard Material/Coating	
	G 150 psi (10,5 bar)				

### TECHNICAL FEATURES

- 
- 2 4 3
- 
- 
- 4 1
- Sun

### PERFORMANCE CURVES

