



**CONFIGURATION**

<b>X</b> Control	Not Adjustable
<b>C</b> Minimum Control Pressure	30 psi (2 bar)
<b>N</b> Seal Material	Buna-N
Material/Coating	

Spring-offset, high-side shuttle cartridges are 2-position valves that have a normal (offset) position that connects the common port (port 3) to work port 4, with work port 2 blocked. When the pressure at port 2 rises above the pressure at port 4, the cartridge shifts to connect the

common port to port 2 with port 4 then blocked.

**TECHNICAL DATA**

Maximum Operating Pressure	5000 psi
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006

**CONFIGURATION OPTIONS**

Model Code Example: **DSEOXCN**

CONTROL	(X)	MINIMUM CONTROL PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		Standard Material/Coating
		<b>E</b> 75 psi (5 bar)		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated