



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                           |
|----------------------------|---------------------------|
| cavidad                    | T-33A                     |
| Series                     | 3                         |
| Capacity                   | 160 L/min.                |
| Maximum Operating Pressure | 350 bar                   |
| Pilot Flow                 | 0,75 L/min.               |
| Valve Hex Size             | 31,8 mm                   |
| Valve Installation Torque  | 203 - 217 Nm              |
| Model Weight               | 0,65 kg                   |
| Seal kit - Cartridge       | Buna: 990-033-007         |
| Seal kit - Cartridge       | Polyurethane: 990-033-002 |
| Seal kit - Cartridge       | Viton: 990-033-006        |
| Seal kit - Cartridge       | Buna: 990-033-007         |
| Seal kit - Cartridge       | Polyurethane: 990-033-002 |
| Seal kit - Cartridge       | Viton: 990-033-006        |

## OPTION SELECTION EXAMPLE: DSGHXGHN

| CONTROL                 | (X) SHIFTING PRESSURE                             | (G) SEAL MATERIAL          | (N) MATERIAL/COATING                                     |
|-------------------------|---|----------------------------|--|
| <b>X</b> Not Adjustable | <b>G</b> 150 psi (10,5 bar)<br>H 200 psi (14 bar) | <b>N</b> Buna-N<br>V Viton | Standard Material/Coating<br>/LH Mild Steel, Zinc-Nickel |

### PERFORMANCE CURVES

