



Low-side (hot oil) shuttle cartridges allow hot oil to be diverted from the low pressure side of a closed loop system. When both work ports (ports 2 and 4) are at equal pressures the valve is spring-centered to an all-ports-blocked position. When one of the work ports (port 2 or 4) sees a higher pressure the opposite work port is connected to the common port (port 3).

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-33A
Series	3
Capacity	40 gpm
Maximum Operating Pressure	5000 psi
Pilot Flow	46 in <sup>3</sup> /min.
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Model Weight	1.65 lb.
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

# OPTION SELECTION EXAMPLE: DSGHXHN

CONTROL	(X) SHIFTING PRESSURE	(H) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	H 200 psi (14 bar) E 75 psi (5 bar) G 150 psi (10,5 bar)	N Buna-N V Viton	Standard Material/Coating /LH Mild Steel, Zinc-Nickel

## TECHNICAL FEATURES

- The spool incorporates a hydraulic stop that eliminates mechanical impact and therefore the potential for internal damage.
- The hydraulic stop results in a small pilot flow from the high side work port (port 2 or 4) to the common port (port 3).
- A unique feature due to the hydraulic stop is that the hot oil relief setting can be confirmed with the transmission in neutral.
- NOTE: Low shift values can potentially result in charge pump pressure alone inadvertently shifting the valve. Use care when selecting shift pressure.
- Although this valve goes into a 4-port cavity, the nose (port 1) is not used.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

## PERFORMANCE CURVES

