



**CONFIGURATION**

X	Control	Not Adjustable
H	Shifting Pressure	200 psi (14 bar)
N	Seal Material	Buna-N
	Material/Coating	

**TECHNICAL DATA**

NOTE:

cavidad	T-33A	DATA
Series	3	MAY
Capacity	160 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Pilot Flow	0,75 L/min.	
Valve Hex Size	31,8 mm	
Valve Installation Torque	203 - 217 Nm	
Model Weight	0.75 kg.	
Seal kit - Cartridge	Buna: 990-033-007	
Seal kit - Cartridge	Polyurethane: 990-033-002	
Seal kit - Cartridge	Viton: 990-033-006	
Seal kit - Cartridge	Buna: 990-033-007	
Seal kit - Cartridge	Polyurethane: 990-033-002	
Seal kit - Cartridge	Viton: 990-033-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: DSGHXHN

CONTROL	(X)	SHIFTING PRESSURE	(H)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		H 200 psi (14 bar)		N Buna-N		Standard Material/Coating
		G 150 psi (10,5 bar)		V Viton		/LH Mild Steel, Zinc-Nickel

## PERFORMANCE CURVES

