



Spring-offset, high-side shuttle cartridges are 2-position valves that have a normal (offset) position that connects the common port (port 3) to work port 4, with work port 2 blocked. When the pressure at port 2 rises above the pressure at port 4, the cartridge shifts to connect the common port to port 2 with port 4 then blocked.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-33A
Series	3
Capacity	60 gpm
Maximum Operating Pressure	5000 psi
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Model Weight	1.96 lb.
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

## OPTION SELECTION EXAMPLE: DSGOXCN

CONTROL	(X) MINIMUM CONTROL PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C 30 psi (2 bar)	N Buna-N V Viton	Standard Material/Coating /LH Mild Steel, Zinc-Nickel

### TECHNICAL FEATURES

- Although this valve goes into a 4-port cavity, the nose (port 1) is not used.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

### PERFORMANCE CURVES

