



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-33A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.@70 bar
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0,65 kg
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	EPDM: 990-033-014
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	EPDM: 990-033-014
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

OPTION SELECTION EXAMPLE: DSGSXCFGN

CONTROL	(X)	SHIFTING PRESSURE	(C)	SEAL MATERIAL	(N)
X Not Adjustable		C 30 psi (2 bar)		N Buna-N	
		F 100 psi (7 bar)		E EPDM	
		G 150 psi (10,5 bar)		V Viton	

PERFORMANCE CURVES

