



CONFIGURATION

X	Control	Not Adjustable
C	Shifting Pressure	30 psi (2 bar)
N	Seal Material	Buna-N

NOTE: DATA MAY VARY FROM TECHNICAL DATA. SEE CONFIGURATION SECTION.

TECHNICAL DATA	
cavidad	T-33A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.@70 bar
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0.90 kg.
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	EPDM: 990-033-014
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

OPTION SELECTION EXAMPLE: DSGSXCN

CONTROL

(X)

SHIFTING PRESSURE

(C)

SEAL MATERIAL

(N)

X Not Adjustable

C 30 psi (2 bar)

N Buna-N

E 75 psi (5 bar)

E EPDM

F 100 psi (7 bar)

V Viton

G 150 psi (10,5 bar)

PERFORMANCE CURVES

