



FLeX 2 2

**CONFIGURATION**

- M \_\_\_\_\_
- H \_\_\_\_\_
- N \_\_\_\_\_
- 912 Deutsch DT04-2P 12 VDC

**TECHNICAL DATA**

NOTE:

	T-8A	DATA
	P	MAY
	28 L/min.	VARY
	350 bar	BY
110 SUS (24 cSt)	0,07 cc/min. @350 bar	
	2,8 - 380 cSt	
	50 ms	
	15,000 max. cycles/hr	
	19,1 mm	
	27 - 33 Nm	
	0.46 kg.	
Seal and nut kit - Coil	Viton: 990-740-006	
Seal kit - Cartridge	Buna: 990-608-007	
Seal kit - Cartridge	Viton: 990-608-006	
#	10,302,201	
Seal kit - Cartridge	Buna: 990-608-007	
Seal kit - Cartridge	Viton: 990-608-006	

- : • O 1 0.75 in. (19 mm)
- Sun
- 2.00 inches (50,8 mm)

CONFIGURATION. SEE  
CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: DTAFMHN912

(M)	(H)	(N)	(912)
<b>M</b>	<b>H</b>	<b>N</b>	
D /	C	E EPDM	
L		V	
T ( )			
X			

## TECHNICAL FEATURES

- Sun
- EPDM
- 1000
- NFPA T2.6.1 R2014
- CFD
- - 1000
- FLeX FLeX
- IP69K
- - 0.004 in<sup>3</sup> (0.07 cc<sup>3</sup>)/min (1 /min)
- D L
- Sun /

## PERFORMANCE CURVES



