



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Manual Override Force Requirement	33 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Seal kit - Cartridge	Buna: 990-413-007
Seal kit - Cartridge	Polyurethane: 990-413-002
Seal kit - Cartridge	Viton: 990-413-006
Seal kit - Cartridge	Buna: 990-413-007
Seal kit - Cartridge	Polyurethane: 990-413-002
Seal kit - Cartridge	Viton: 990-413-006

CONFIGURATION OPTIONS

Model Code Example: DTCFXCN

CONTROL (X)	POPPET CONFIGURATION (C)	SEAL MATERIAL (N)	BOBINA (812)
X No Manual Override	C normalmente cerrado	N Buna-N	No Coil
D Twist/Lock (Dual) Manual Override		E EPDM	
L Twist/Lock (Detent) Manual Override		V Viton	
M activador manual			
T Twist (Momentary) Manual Override			