



2 2

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|-------------------------|---------------------------|
| | T-13A |
| | 1 |
| | 23 L/min. |
| | 350 bar |
| 110 SUS (24 cSt) | 0,7 cc/min.@350 bar |
| | 2,5 mm |
| | 33 N/100 bar @ Port 1 |
| | 50 ms |
| | 15,000 max. cycles/hr |
| | 16 mm |
| | 22,2 mm |
| | 41 - 47 Nm |
| | 0.24 kg. |
| Seal and nut kit - Coil | Viton: 990-740-006 |
| Seal kit - Cartridge | Buna: 990-413-007 |
| Seal kit - Cartridge | Polyurethane: 990-413-002 |
| Seal kit - Cartridge | Viton: 990-413-006 |
| Seal kit - Cartridge | Buna: 990-413-007 |
| Seal kit - Cartridge | Polyurethane: 990-413-002 |
| Seal kit - Cartridge | Viton: 990-413-006 |

- : • Sun
- 2.00 inches (50,8 mm)

OPTION SELECTION EXAMPLE: DTCFXCN

| (X) | (C) | (N) | |
|----------|----------|----------|--|
| X | C | N | |
| D / | | E EPDM | |
| L | | V | |
| M | | | |
| T () | | | |

TECHNICAL FEATURES

- 5000 psi (350 bar)
-
- 10 / @5000 psi 0,7 cc/min @ 350 bar
- IP69K
- " "
- /
-
- D L
- /
-
-
- Sun /

PERFORMANCE CURVES

