



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	SC-08-02
Series	0C
Capacity	23 L/min.
Maximum Operating Pressure	250 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	15 drops/min.@3600 psi
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	.51 in.
Coil Nut Torque	4,8 - 5,3 Nm
Valve Hex Size	22,2 mm
Valve Installation Torque	28 - 31 Nm
Model Weight	0,15 kg
Seal kit - Cartridge	Buna: 99C-083-007
Seal kit - Cartridge	Viton: 99C-083-006
Seal kit - Cartridge	Buna: 99C-083-007
Seal kit - Cartridge	Viton: 99C-083-006

OPTION SELECTION EXAMPLE: DTTAXCN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)	BOBINA	(924D)
X No Manual Override		C normalmente cerrado		N Buna-N		No Coil	
L Manual Override (Push with Detent)							

PERFORMANCE CURVES

