



FLex 2 3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-150A
	0
	23 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min. @350 bar
	50 ms
	10,000 max. cycles/hr
	16 mm
	19,1 mm
	35 - 40 Nm
	0.19 kg.
Seal and nut kit - Coil	Viton: 990-740-006
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006
#	10,302,201
Seal kit - Cartridge	Buna: 990-150-007
Seal kit - Cartridge	Viton: 990-150-006

- : • Sun
- 2.00 inches (50,8 mm)
- SUN (50° C) (580 mA) 15%

# OPTION SELECTION EXAMPLE: DWBFXAN

	(X)	(A)	(N)
<b>X</b>	A 1-2 2-3	N	
<b>D</b> /	N 2-3 1-2	E EPDM	
<b>L</b>		V	
<b>M</b>			
<b>T</b> ( )			

## TECHNICAL FEATURES

- 
- 
- 3 1
- 1000
- NFPA T2.6.1 R2014
- CFD
- - 1000
- IP69K
- - 0.004 in<sup>3</sup> (0.07 cc<sup>3</sup>)/min (1 /min)
- A (DWBF-\*A\*) 25 lbf (110 N)
- D L
- 
- 
- 
- Sun /

## PERFORMANCE CURVES

