



CONFIGURATION

X	Control	No Manual Override
A	Poppet Configuration	Normally Open 1 to 2, Closed 2 to 3
N	Seal Material	Buna-N
	bobina	

TECHNICAL DATA

NOTE:

cavidad	T-11A	DATA
Series	1	MAY
Capacity	30 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Manual Override Force Requirement	33 N/100 bar @ Port 1	
Manual Override Stroke	2,5 mm	
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar	
Response Time - Typical	50 ms	
Switching Frequency	15,000 max. cycles/hr	
Solenoid Tube Diameter	16 mm	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Seal and nut kit - Coil	Viton: 990-740-006	
Seal kit - Cartridge	Buna: 990-411-007	
Seal kit - Cartridge	Viton: 990-411-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: DWDFXAN

CONTROL	(X)	POPPET CONFIGURATION	(A)	SEAL MATERIAL	(N)	BOBINA	(JN23BD)
X No Manual Override		A Normally Open 1 to 2, Closed 2 to 3		N Buna-N		No coil	
D Twist/Lock (Dual) Manual Override				E EPDM			
L Twist/Lock (Detent) Manual Override				V Viton			
M activador manual							
T Twist (Momentary) Manual Override							

PERFORMANCE CURVES

