



This manually operated, 2-position, 3-way directional cartridge is a direct-acting, poppet-style valve used to control the direction of flow in a hydraulic circuit. The valve is normally open between port 1 and port 2 with port 3 blocked. Operating the valve connects port 2 to 3 and blocks port 1. All flow paths are bidirectional and blocked paths are blocked in both directions. Due to the poppet style construction, this valve has extremely low leakage. Manual operation is achieved via Sun's Twist/Lock manual override mechanism and is designed for intermittent (infrequent) use only.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-11A
Series	1
Capacity	7.5 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	10 drops/min.@5000 psi
Operating Torque	10 lbf in.
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006

OPTION SELECTION EXAMPLE: DWDMAN

POPPET CONFIGURATION

(A)

SEAL MATERIAL

(N)

A Normally Open 1 to 2, Closed 2 to 3

N Buna-N

E EPDM

V Viton

TECHNICAL FEATURES

- This valve is designed for intermittent use such as a manual override. The manual control assembly has a mechanical life expectancy of approximately 7,000 cycles.
- The momentary/twist control option "T" allows the operator to momentarily shift the valve by twisting the knob clockwise and releasing. Once released, the valve returns to its normal position.
- The detent/lock control option "L" allows the operator to shift the valve into a mechanically detented position by twisting the knob counter-clockwise. This detented position will be maintained until the operator twists the knob clockwise and allows the valve to return to its normal position. Please note that the detented position is for temporary shifting only and not intended to be a permanent detent.
- The dual-operation control option "D" allows the operator to either shift the valve momentarily by twisting the knob clockwise or shift it into a mechanically detented position by twisting counter-clockwise. Please note that the detented position is for temporary shifting only and not intended to be a permanent detent.
- The control on this valve is meant to be operated by a person's hand. The control should not be modified, for instance fastening a lever to the knob. Under no circumstances should the control be operated by other mechanical devices.
- Valves exhibit extremely low leakage rates; less than 10 drops/min. @ 5000 psi (0,7 cc/min @350 bar).
- This valve is suitable for load holding on port 3 only. The detent mechanism in the manual override is meant for temporary actuation.
- Incorporates the Sun floating-style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

