



CONFIGURATION

NOTES:
 • **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

MODIFIER

(IT3)

- IT3** 65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer
- 6061-T651 Aluminum, Buna-N
- I11** 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- I10** 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- IM** 6061-T651 Aluminum, Metric, Buna-N
- I1B** 6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- I1A** 6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- IS** 65-45-12 Ductile Iron, Buna-N, Dewatering Oil
- IS4** 65-45-12 Ductile Iron, Buna-N, Chem. Black
- IS3** 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
- IT** 65-45-12 Ductile Iron, Metric, Buna-N, Dewatering Oil
- IT4** 65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black