



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-5A
Series	2
Capacity	45 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.17 kg.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: FCDBXAN

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	N Buna-N	Standard Material/Coating
K manilla	B Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)	V Viton	/AP Stainless Steel, Passivated
L Tuning Adjustment			/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

