



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-5A
Series	2
Capacity	45 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0,20 kg
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: FCDCLXAN

CONTROL	(L) FLOW RATE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A .106 gpm (.4 L/min.)	N Buna-N	
C Tamper Resistant - Factory Set	B .264 gpm (1.0 L/min.)	V Viton	
K manilla	C .528 gpm (2.0 L/min.)		
X Not Adjustable	D .793 gpm (3.0 L/min.)		
	F .991 gpm (3.75 L/min.)		
	G 1.215 gpm (4.6 L/min.)		
	H 1.479 gpm (5.6 L/min.)		
	J 1.823 gpm (6.9 L/min.)		
	K 2.245 gpm (8.5 L/min.)		
	L 2.774 gpm (10.5 L/min.)		
	M 3.434 gpm (13.0 L/min.)		
	N 4.227 gpm (16.0 L/min.)		
	P 5.178 gpm (19.6 L/min.)		
	R 6.472 gpm (24.5 L/min.)		
	S 7.925 gpm (30.0 L/min.)		
	T 9.774 gpm (37.0 L/min.)		
	V 11.888 gpm (45.0 L/min.)		

PERFORMANCE CURVES

