



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-16A
Series	3
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.43 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

# OPTION SELECTION EXAMPLE: FCEBXAN

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>A</b> Replaceable Orifice .2 - 25 gpm (0,8 - 95 L/min.)	<b>N</b> Buna-N	Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set	<b>B</b> Permanent Orifice .2 - 25 gpm (0,8 - 95 L/min.)	<b>V</b> Viton	<b>/AP</b> Stainless Steel, Passivated
<b>K</b> manilla			<b>/LH</b> Mild Steel, Zinc-Nickel
<b>L</b> Tuning Adjustment			

## PERFORMANCE CURVES

