



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

**CONFIGURATION OPTIONS**

**Model Code Example: FCFBXAN**

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>A</b> Replaceable Orifice .2 - 50 gpm (1 - 200 L/min.)		<b>N</b> Buna-N		Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set		<b>B</b> Permanent Orifice .2 - 50 gpm (1 - 200 L/min.)		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
<b>K</b> manilla						
<b>L</b> Tuning Adjustment						