



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-16A
	3
	95 L/min.
	350 bar
	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.59 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: FDEALAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A .2 - 25 gpm (0,8 - 95 L/min.)	N	Standard Material/Coating	
H	B .2 - 16 gpm (0,8 - 60 L/min.)	E EPDM	/LH	-
		V		

TECHNICAL FEATURES

- 2
-
-
- 0.2gpm 0.8 L/min
- EPDM

PERFORMANCE CURVES

