



PROPORTIONAL PERFORMANCE DATA

	B-spool: 10%, C-spool: 9%
	3%
()	1.5%
	100 Hz
	B-spool: 35%, C-spool: 35%
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	Viton: 990-016-006

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-16A
	3
	120 L/min.
	350 bar
	2,8 - 380 cSt
	50 ms
	3,600 max. cycles/hr
	16 mm
	31,8 mm
	203 - 217 Nm
	2.22 kg.
Seal and nut kit - Coil	Viton: 990-740-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: FDEPXBN

(X)	(B)	(N)	(N)
X	B 11 gpm (42 L/min.) C 19 gpm (72 L/min.)	N E EPDM V	

TECHNICAL FEATURES

- NFPA T2.6.1 R2014
- CFD
- - 1000
- IP69K
- FLeX
- SUN XMD
-
-
- 500
- 80 - 250 Hz

PERFORMANCE CURVES

