



2 2 . 2 3 1 2 3 1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	20 L/min.
	350 bar
	0,33 cc
110 SUS (24 cSt)	30 cc/min.@70 bar
	7 bar
	0,8 mm
	± 2 %
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.26 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: FKBBXCN

(X)	(C)	(N)	MATERIAL/COATING
X	C	N	Standard Material/Coating
L		V	/AP
			/LH -

TECHNICAL FEATURES

- L
 - LR*C-XHN
 - LP*C-XHN
 - 1 4 500psi 35bar
 - 4 1
 - Sun
- 50-450psi 3.5-30bar 100psi 7bar

PERFORMANCE CURVES

