



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-21A
Series	1
Capacity	34 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Minimum Pilot Pressure to Operate	7 bar
orificio de desvío	0,8 mm
Pilot Volume Displacement	0,33 cc
Hysteresis	± 2 %
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0,15 kg
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: FKCBLXCXN

CONTROL

(L) SPOOL CONFIGURATION

(C) SEAL MATERIAL

(N)

L Standard Screw Adjustment

C normalmente cerrado

N Buna-N

X Not Adjustable

V Viton

PERFORMANCE CURVES

