



PORT 4 DRAIN PORT 3 VALVE PORT 2 VALVE

2 2 . 2 3 1 2 3 1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	120 L/min.
	350 bar
	1,6 cc
110 SUS (24 cSt)	65 cc/min.@70 bar
	7 bar
	± 2 %
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

OPTION SELECTION EXAMPLE: FKGAXCN

(X)

(C)

(N)

X

C

N

L

E EPDM
V

TECHNICAL FEATURES

- LR*C-XHN LP*C-XHN
- 1 4 500psi 35bar
- 4 1
- L 50-250psi 3.5-15bar 100psi 7bar
- EPDM
- Sun

PERFORMANCE CURVES

