



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-24A
Series	4
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	98 cc/min. @70 bar
Minimum Pilot Pressure to Operate	7 bar
orificio de desvío	0,8 mm
Pilot Volume Displacement	3,3 cc
Hysteresis	± 2 %
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	1.30 kg.
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

OPTION SELECTION EXAMPLE: FKIBXCEN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N)
X Not Adjustable	C normalmente cerrado	N Buna-N	
L Tuning Adjustment		E EPDM	
		V Viton	

PERFORMANCE CURVES

