



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                           |
|----------------------------|---------------------------|
| cavidad                    | T-13A                     |
| Series                     | 1                         |
| Capacity                   | 40 L/min.                 |
| Maximum Operating Pressure | 350 bar                   |
| Valve Hex Size             | 22,2 mm                   |
| Valve Installation Torque  | 41 - 47 Nm                |
| Seal kit - Cartridge       | Buna: 990-010-007         |
| Seal kit - Cartridge       | EPDM: 990-010-014         |
| Seal kit - Cartridge       | Polyurethane: 990-010-002 |
| Seal kit - Cartridge       | Viton: 990-010-006        |

# OPTION SELECTION EXAMPLE: FLDAXDN

| CONTROL          | (X) FILTER RATING                  | (D) SEAL MATERIAL | (N) MATERIAL/COATING            |
|------------------|------------------------------------|-------------------|---------------------------------|
| X Not Adjustable | D 40 Micron Nominal (Surface type) | N Buna-N          | Standard Material/Coating       |
|                  |                                    | E EPDM            | /AP Stainless Steel, Passivated |
|                  |                                    | V Viton           | /LH Mild Steel, Zinc-Nickel     |

## PERFORMANCE CURVES

