



Sun

2 1

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-16A
	3
	160 L/min.
	350 bar
	31,8 mm
	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

: •  
•

# OPTION SELECTION EXAMPLE: FLHAXDN

	(X)	(D)	(N)	MATERIAL/COATING
<b>X</b>	<b>D</b> 40 ( )	<b>N</b>	Standard Material/Coating	
	A 3 ( )	E EPDM	/AP	
	B 10 ( )	V	/LH	
	C 25 ( )			
	Z 1 ( )			

## TECHNICAL FEATURES

- 3000 psid 210 bar
- 2 1
- EPDM
- 
- 304 304
- 40 63
- 
- 
- 
- 
- 3 10 25
- 3 10 25 Beta

## PERFORMANCE CURVES

FILTRATION RATIO PER ISO 16889				
MICRON RATING	B <sub>X(C)</sub> ≥75 (98.7%)	B <sub>X(C)</sub> ≥100 (99.0%)	B <sub>X(C)</sub> ≥200 (99.5%)	B <sub>X(C)</sub> ≥1000 (99.9%)
1	<4.0	<4.0	<4.0	4.2
3	<4.0	<4.0	<4.0	4.8
10	6.8	7.1	8.0	10.0
25	16.3	17.1	19.0	24.0



