



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006

CONFIGURATION OPTIONS

Model Code Example: FMDAXCDN

CONTROL	(X)	FLOW RATE	(C)	SEAL MATERIAL	(N)	BOBINA
X No Manual Override		C .1 - 6 gpm (0,4 - 23 L/min.)		N Buna-N		No coil
D Twist/Lock (Dual) Manual Override		A .1 - 1.6 gpm (0,4 - 6.1 L/min.)		E EPDM		224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
E Twist (Extended) Manual Override		B .1 - 4 gpm (0,4 - 15 L/min.)		V Viton		224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
L Twist/Lock (Detent) Manual Override		D .1 - 9 gpm (0,4 - 34 L/min.)				912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
M activador manual						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
T Twist (Momentary) Manual Override						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver